

# HOSE, EVA TUBING & NH3 GAUGES

## Black EPDM Hose

- This black neoprene hose for transfer of NH3 is reinforced with a fabric applicator or stainless steel braid.
- This high pressure NH3 hose handles working pressures for conveying NH3 from up to 350 psi, with a 5:1 safety factor (1750 psi minimum burst).

Part Number	Size	Working Pressure
N2000-1	1"	350 PSI
N2595-3/4	3/4"	
N2595-1	1"	
N2595-1-1/4	1-1/4"	
N2595-2	2"	
N1446-1/2	1/2"	
N1446-3/4	3/4"	
N1446-1-1/4	1-1/4"	
N1446-1-1/2	1-1/2"	
N1446-2	2"	
N1446-3	3"	



## Eva Tubing

Part Number	Size	Colour	Working Pressure
N24	3/8"	Blue	120 PSI
N25	1/2"	Blue	120 PSI
N25B	1/2"	Black	120 PSI
512518	1" (Braided)	White	75 PSI



## Sight Gauge Hose

Part Number	Size	Colour
N88	1/2"	Clear
N89	5/8"	Clear
N90	3/4"	Clear



## Hose Cutters

Part Number	Description
B8993	Hose Cutters
B8983	Replacement Blade



## Nylon Braid NH3 Hose N2000

N2000 is a premium grade hose within an 6-year removal date, 6-year service life and a 6-year prorated warranty with a full warranty for the first 3 years. Black EPDM tube and cover with green longitudinal strip. Nylon Braid.



## Nylon Braid NH3 Hose N2595

N2595 is a super premium hose with an 8-year removal date, 8-year service life and an 8-year prorated warranty. Butyl tube and black neoprene cover. Stainless braid.



## Nylon Braid NH3 Hose N1446

N1446 is a super premium hose with an 10-year removal date, 10-year service life and a 10-year prorated warranty with a full warranty for the first 5 years. Butyl tube and black neoprene cover with green spiral strip. Stainless braid. Recommended for riser use and other high stress applications.



WW0160



WW0164

## Ammonia Gauges

Part Number	Size	PSI	PSI
WW0160	2-1/2"	0-60	Dry
WW0162	2-1/2"	0-150	Dry
WW0164	2-1/2"	0-400	Dry
WW0260	4"	0-60	Dry
WW0262	4"	0-160	Dry
WW0264	4"	0-400	Dry
WGGSS400	2-1/2"	0-400	Liquid

NOTE: All gauges are 1/4" NPT